



RadioProcessor™USB

Power Supply

Owner's Manual



RadioProcessor™ USB Power Supply

**Congratulations and *thank you* for choosing a design from
SpinCore Technologies, Inc.**

We appreciate your business!

**At SpinCore we try to fully support the needs of our customers. If you
are in need of assistance, please contact us and we will strive to provide
the necessary support.**

© 2007 - 2011 SpinCore Technologies, Inc. All rights reserved.

SpinCore Technologies, Inc. reserves the right to make changes to the product(s) or information herein without notice. RadioProcessor™, PulseBlaster™, SpinCore, and the SpinCore Technologies, Inc. logos are trademarks of SpinCore Technologies, Inc. All other trademarks are the property of their respective owners.

SpinCore Technologies, Inc. makes every effort to verify the correct operation of the equipment. This equipment version is not intended for use in a system in which the failure of a SpinCore device will threaten the safety of equipment or person(s).

Table of Contents

I. Overview.....	4
II. Connector Information.....	5
Input Connector	5
Output Connector	5
Cable Information	6
III. Contact Information.....	7

I. Overview

The RadioProcessor™ USB Power Supply generates +5V/2A, +6V/1A and -6V/0.2A output voltages with a low ripple factor as required by the RadioProcessor™ USB board. The RadioProcessor™ USB Power Supply can operate under two different configurations depending on the input power sources:

1. Single input of 12V for triple DC/DC conversion:

In this configuration, the RadioProcessor™ USB Power Supply converts the 12 V input voltage into three regulated 5V/2A, +6V/1A and -6V/0.2A output voltages. The RadioProcessor™ USB Power Supply has a wide input voltage range of 7.5 V-16 V in this configuration. This is the standard model and is suitable for most applications.

2. Dual input of 12V and 5V for dual DC/DC conversion:

In this configuration, the RadioProcessor™ USB Power Supply converts the +12 V input voltage into +6V/1A and -6V/0.2A output voltages and takes 5V/2A directly from the +5 V input source. Please specify if you have dual inputs available and would prefer this model, SpinCore will be glad to provide.

The DC/DC voltage conversion circuit design utilizes switch-mode technology to achieve high power conversion efficiency and thus decreasing the operating temperature.

The 4-pin input connector is compatible with standard 12 V and 5 V PC power supply connectors. The 6-pin output connector is pin-compatible with the power connector of RadioProcessorUSB boards, facilitating a simple 1:1 cable connection between boards.

The physical size of the board is approximately 5 cm by 10 cm.

II. Connector Information

Input Connector

The RadioProcessor-USB™ Power Supply has one 4-pin input connector. The pin and signal arrangements for this connector are shown below in Figure 1.




Figure 1: 4-Pin Input Connector

Part number: 53109-0410 (Mouser 538-531-09-0410)

Output Connector

The RadioProcessor-USB™ Power Supply has one 6-pin output connector. The pin and signal arrangements for this connector are shown below in Figure 2.




Figure 2: 6-pin Output Connector

Part number: 39-28-8060 (Digi-Key WM23802-ND)

RadioProcessor™ USB Power Supply

Cable Information

If you will be making your own power supply cable to connect to the 6-pin output connector, you will need the following parts or their equivalents: One 6-pin female Mini-Fit Jr.™ connector (DigiKey part No. WM23702-ND) and six Mini Fit Jr.™ crimp receptacles (Digikey part No. WM2501-ND).

III. Contact Information

SpinCore Technologies, Inc.
4631 NW 53rd Avenue, SUITE 103
Gainesville, FL 32653
USA

Telephone (USA): 352-271-7383
Fax (USA): 352-371-8679
Website: <http://www.spincore.com>
Web Contact Form: <http://spincore.com/contact.shtml>